

KITTEC® PROFESSIONAL-LINE

Modellen **X** Professional Line X Laden Top lader Energie Elektrisch

Model	Voorm	Binnenafmetingen					Buitenafmetingen						TempMax [°C]	Vermogen [kW]	Spanning [V]	Stroom [A]	Gewicht [kg]
		Ø [mm]	Breedte [mm]	Diepte [mm]	Hoogde [mm]	Inhoud [L]	Breedte [mm]	Diepte [mm]	Hoogde [mm]	Diepte bij geopend deksel [mm]	Hoogte met gedraaid onderstel [mm]	Hoogte tot opening oven [mm]					
X 45	rond	430	-	-	325	47	700	785	1020	1030	-	-	1320	3,6	230 N~	16	75
X 45 S	rond	430	-	-	325	47	700	785	1020	1030	-	-	1320	4,4	400 2N~	2x10 CEE16	75
X 55	rond	430	-	-	400	58	700	785	1020	1030	-	-	1280±30	3,6	230 N~	16	85
X 55 S	rond	430	-	-	400	58	700	785	1020	1030	-	-	1320	4,4	400 2N~	2x10 CEE16	85
X 65	rond	430	-	-	480	69	700	785	1020	1030	-	-	1250±30	3,6	230 N~	16	90
X 65 S	rond	430	-	-	480	69	700	785	1020	1030	-	-	1320	5,6	400 2N~	2x12 CEE16	90
X 75	rond	430	-	-	555	79	700	785	1020	1030	-	-	1200±30	3,6	230 N~	16	95
X 75 S	rond	430	-	-	555	79	700	785	1020	1030	-	-	1320	5,6	400 2N~	2x12 CEE16	95
X 85	rond	510	-	-	400	82	780	865	1020	1110	-	-	1200±30	3,6	230 N~	16	90
X 85 S	rond	510	-	-	400	82	780	865	1020	1110	-	-	1320	5,6	400 2N~	2x12 CEE16	90
X 100 S	rond	510	-	-	480	98	780	865	1020	1110	-	-	1320	6,8	400 3N~	3x10 CEE16	105
X 115 S	rond	510	-	-	555	113	780	865	1020	1110	-	-	1320	6,8	400 3N~	3x10 CEE16	110
X 135 S	rond	590	-	-	480	132	860	945	1020	1180	-	-	1320	8,2	400 3N~	3x12 CEE16	125
X 170 S	rond	590	-	-	630	172	860	945	1020	1180	-	-	1320	11	400 3N~	3x16 CEE16	140
X 195 S	rond	590	-	-	710	194	860	945	1020	1180	-	-	1320	11	400 3N~	3x16 CEE16	150
X 215 S	rond	590	-	-	780	213	860	945	1020	1180	-	-	1320	11	400 3N~	3x16 CEE16	160
X 240 S	rond	690	-	-	645	241	980	1085	1020	1330	-	-	1320	14	400 3N~	3x20 CEE32	160
X 270 S	rond	690	-	-	710	266	980	1085	1020	1330	-	-	1320	16	400 3N~	3x23 CEE32	170
X 300 S	rond	690	-	-	780	293	980	1085	1020	1330	-	-	1320	18	400 3N~	3x26 CEE32	180