



KITTEC® STUDIO-LINE

Model series **CB Studio Line CB**

page 1: 230V-models

[Loading](#) [top loading](#) [Energy](#) [electric](#)

Model	Vorm	Binnenafmetingen					Buitenafmetingen						TempMax [°C]	Vermogen [kW]	Spanning [V]	Stroom [A]	Gewicht [kg]
		Ø [mm]	Breedte [mm]	Diepte [mm]	Hoogte [mm]	Inhoud [L]	Breedte [mm]	Diepte [mm]	Hoogte [mm]	Diepte bij geopend deksel [mm]	Hoogte met gedraaid onderstel [mm]	Hoogte tot opening oven [mm]					
CB 20	round	330	-	-	230	20	520	650	545	-	-	-	1320	3	230 N~	13	30
CB 40	round	400	-	-	305	40	590	720	620	-	780	-	1320	3,6	230 N~	16	50
CB 50	round	400	-	-	380	50	590	720	700	-	860	-	1280±30	3,6	230 N~	16	55
CB 50 PLUS	round	400	-	-	380	50	590	720	720	-	880	-	1320	3,6	230 N~	16	55
CB 50 Double	round	400	-	-	380	50	590	720	740	-	900	-	1320	3,6	230 N~	16	60
CB 60	round	400	-	-	460	60	590	720	780	-	940	-	1230±30	3,6	230 N~	16	60
CB 60 PLUS	round	400	-	-	460	60	590	720	800	-	960	-	1280±30	3,6	230 N~	16	60
CB 60 Double	round	400	-	-	460	60	590	720	820	-	980	-	1320	3,6	230 N~	16	65
CB 66	round	400	-	-	535	66	590	720	850	-	1010	-	1200±30	3,6	230 N~	16	60
CB 66 PLUS	round	400	-	-	535	66	590	720	870	-	1030	-	1250±30	3,6	230 N~	16	60
CB 66 Double	round	400	-	-	535	66	590	720	890	-	1050	-	1290±30	3,6	230 N~	16	65
CB 70 PLUS	round	430	-	-	460	70	620	750	780	-	1030	-	1230±30	3,6	230 N~	16	60
CB 70 Double	round	430	-	-	460	70	620	750	800	-	1050	-	1290±30	3,6	230 N~	16	65
CB 80 PLUS	round	510	-	-	380	80	700	830	700	-	1030	-	1200±30	3,6	230 N~	16	65
CB 80 Double	round	510	-	-	380	80	700	830	720	-	1050	-	1250±30	3,6	230 N~	16	70
CB 95 PLUS	round	510	-	-	460	94	700	830	800	-	1110	-	1150±30	3,6	230 N~	16	80
CB 95 Double	round	510	-	-	460	94	700	830	820	-	1130	-	1210±30	3,6	230 N~	16	85



Model series **CB Studio Line CB**

page 2: 400V-models

[Loading](#) [top loading](#) [Energy](#) [electric](#)

Model	Vorm	Binnenafmetingen					Buitenafmetingen						TempMax [°C]	Vermogen [kW]	Spanning [V]	Stroom [A]	Gewicht [kg]
		Ø [mm]	Breedte [mm]	Diepte [mm]	Hoogte [mm]	Inhoud [L]	Breedte [mm]	Diepte [mm]	Hoogte [mm]	Diepte bij geopend deksel [mm]	Hoogte met gedraaid onderstel [mm]	Hoogte tot opening oven [mm]					
CB 50 S	round	400	-	-	380	50	590	720	700	-	860	-	1320	4,4	400 2N~	2x11 CEE16	55
CB 60 S	round	400	-	-	460	60	590	720	780	-	940	-	1320	5	400 2N~	2x13 CEE16	60
CB 66 S	round	400	-	-	535	66	590	720	850	-	1010	-	1320	5	400 2N~	2x13 CEE16	60
CB 70 S	round	430	-	-	460	70	620	750	780	-	1010	-	1320	5,6	400 2N~	2x12 CEE16	60
Expansion ring f CB70 S	round	430	-	-	230	30	620	750	230	-	-	-	-	3	-	-	25
CB 100 S	round	430	-	-	690	100	620	750	1010	-	-	-	1320	8,6	400 3N~	3x12 CEE16	85
CB 80 S	round	510	-	-	380	80	700	830	700	-	1010	-	1320	5,6	400 2N~	2x12 CEE16	65
Expansion ring f CB80 S	round	510	-	-	230	47	700	830	230	-	-	-	-	3	-	-	25
CB 120 S	round	510	-	-	610	120	700	830	930	-	-	-	1320	8,6	400 3N~	3x12 CEE16	90
CB 95 S	round	510	-	-	460	94	700	830	780	-	1090	-	1320	7	400 2N~	2x16 CEE16	80
Expansion ring f CB95 S	round	510	-	-	230	47	700	830	230	-	-	-	-	3,7	-	-	25
CB 140 S	round	510	-	-	690	141	700	838	1010	-	-	-	1320	10,7	400 3N~	2x16 CEE16	105
CB 130 S	round	590	-	-	460	130	780	910	800	-	1030	-	1320	7,2	400 2N~	2x16 CEE16	105
Expansion ring f CB130	round	590	-	-	230	60	780	910	230	-	-	-	-	3,8	-	-	30
CB 190 S	round	590	-	-	690	190	780	910	1030	-	-	-	1320	11	400 3N~	3x16 CEE16	135
CB 200 S	round	690	-	-	535	200	880	1010	850	-	-	-	1320	12	400 3N~	3x26 CEE32	145
Expansion ring f CB200	round	690	-	-	230	100	880	1010	230	-	-	-	-	6	-	-	35
CB 300 S	round	690	-	-	765	300	880	1010	1080	-	-	-	1320	18	400 3N~	3x26 CEE32	180
CB 220 S	oval	-	820	590	535	220	1020	930	850	-	1010	-	1320	15	400 3N~	3x22 CEE32	180
CB 330 S	oval	-	930	590	690	330	1130	930	1010	-	-	-	1320	18	400 3N~	3x26 CEE32	220
CB 380 S	oval	-	1045	590	690	380	1250	930	1010	-	-	-	1320	19	400 3N~	3x28 CEE32	230
CB 460 S	oval	-	1030	690	765	466	1235	1030	1080	-	-	-	1320	21	400 3N~	3x31 CEE32	245
CB 520 S	oval	-	1145	690	765	525	1350	1030	1080	-	-	-	1320	22	400 3N~	3x32 CEE32	260